



# HT54-18X(ND)-F

415W/420W/425W

430W/435W



**PRODUCT WARRANTY**



**LINEAR POWER WARRANTY**



Half cut cell technology can reduce the internal power loss and improve module overall power. Excellent heat dissipation avoids hot spot production.

The optimized number and width of main gate lines, maximize the light receiving area of modules and reduce module power consumption

Designed for high voltage systems of up to 1500 VDC, increasing the string length of solar systems and saving on BoS costs.

Microcrack resistant Double glass structure enhance reliability, double EL tested of high quality control.

Entire module certified to with stand extreme wind (2400 Pa) and snow loads (5400 Pa).

All the modules are sorted and packaged by amperage, reducing mismatch losses and maximizing system output.

**0~+3%** Positive tolerance 0~+3% guaranteed

Anti **PID** PID resistant



Reliable State - Owned Enterprise Deliver Solar Power Since 1960s

Comprehensive and first-rate certification system  
IEC 61215:2016, IEC 61730:2016 Latest Standard  
ISO 9001 ISO 14001 and ISO 45001, meeting the highest international standards  
Strict quality control

Factory:  
Lianyungang Shenzhou New Energy CO., Ltd.  
[www.HT-LYG.COM](http://www.HT-LYG.COM)

\* Copyright@2023V2 Specifications are subject to change without further notification